

Drywall Screw, TEX

Technogips Pro Drywall Screw TEX with a sharpened point is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. The collective thickness all joint elements up to 1,2 mm.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 4.2 x 13 mm






Standard Classification:

In compliance with EN 14566:2008, Type LN



Advantages:

-  ✓ PH 2 screw bit included in every box
-  ✓ The mushroom head of the screw ensures added strength to the fastening of the joint elements.
-  ✓ Sharpened point and special thread ease the puncture of the metal profile


Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Packaging and Storage:

Product	d _w x L _w	Box	Boxes in a carton
Drywall Screw TEX 4.2 x 13	4.2 x 13 mm	1000 pcs	12 units

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area



Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©