

Rotary Hanger, Moon Type

Rotary hanger Moon type for suspension of CD 60 Premium profile structure to the main ceiling (concrete, wooden grid, etc.).

Specially designed, arched lower half of the hanger, for increased stability in a 4-point tie to CD 60 profile. The spring positioned in the upper half has two pre-cut surface holes of Ø 4mm to ensure a secure fixing to the Wire with Hook and Eye, while simultaneously it ensures an easy and precise levelling of the construction.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Metal thickness: 0.8 mm

Standard Classification:

In compliance with EN 13964:2014

Advantages:

- ✓ 4-point tie to profile CD 60
- ✓ Recommended load-bearing capacity of max 0.25 kN
- ✓ A stable spring for a precise levelling of the suspended ceiling level
- ✓ Quick and easy installation



Technical Data:

Parameters:	Specification:
Steel Thickness	0.8 mm
Material fire reaction class:	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.25 kN
Max. Load-bearing capacity admF	0.30 kN

Packaging and Storage:

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. April 2020©