

Acoustic foam tape

Self-adhesive acoustic tape for sealing the space between the peripheral profile and the solid floor, ceiling or wall.

The acoustic tape improves effectively sound proofing of premises by stopping the spread of impact noise and vibration from the floor and ceiling.

The width of the acoustic tape should be consistent with the type of metal profiles as follows:

- ✓ Profile UD 27 → Acoustic tape 30 mm
- ✓ Profile CW / UW 50 → Acoustic tape 45 mm
- ✓ Profile CW / UW 75 → Acoustic tape 65 mm
- ✓ Profile CW / UW 100 → Acoustic tape 90 mm



Advantages:

- ✓ Easy and quick processing by roll-out.
- ✓ High elasticity.
- ✓ High resistance to water, moisture, mold, oxidation, atmospheric and climatic influences.

Packaging and Storage:

Product	Thickness	Length	Box
Acoustic foam tape 30	3 mm	30 m	34 rolls
Acoustic foam tape 45	3 mm	30 m	20 rolls
Acoustic foam tape 65	3 mm	30 m	14 rolls
Acoustic foam tape 90	3 mm	30 m	10 rolls

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, to prevent the risk of sticking glue to the fingers.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©