


Adjusting bracket 125 Super Premium C5



Product description:

Adjusting bracket with high resistance against corrosion for direct suspension of CD 60 profile to solid walls and ceilings.

Standard Classification:

In compliance with **EN 13964:2014**
 Category for Protection Against Corrosion, acc. EN ISO 12944-2:
Class C5 Highest Level of Protection



Advantages:


- ✓ Load carrying capacity (min 0.40 kN)
- ✓ Uniform metal thickness of 0.9 mm, for added strength
- ✓ Easy levelling due to the shoulder positioned service holes
- ✓ Minimized loss of useful space in the room

Aggressive Environment Examples - Class C5:

- External
 - Industrial zones, coastal areas and buildings near the beach with high levels of salt in the air.
- Internal
 - Buildings and areas subject to constant condensation, intense humidity and high levels of pollutants e.g. sea water or thermal baths.

Technical Data:

Parameters:	Value:
Steel thickness	0.8 mm
Reaction to fire	A1
Corrosion resistance class	Class B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.60 kN



Packaging and Storage:

Product	Dimensions L _w / d _w	Thickness	Box
Adjusting Bracket Super premium C5	120 / 60 mm	0.9 mm	100 pcs

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered and ventilated area.

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2021©