


# CD Cross Connector Super Premium C5

**Product description:**

CD cross connector with high resistance against corrosion for securing a strong cross-tie between the load carrying and fastened CD 60 profile in constructing double level suspended ceilings.

Steel thickness: 0.9 mm



**Standard Classification:**

In compliance with **EN 13964:2014**  
 Category for Protection Against Corrosion, acc. EN ISO 12944-2:  
**Class C5 Highest Level of Protection**



**Aggressive Environment Examples - Class C5:**

- External
  - Industrial zones, coastal areas and buildings near the beach with high levels of salt in the air.
- Internal
  - Buildings and areas subject to constant condensation, intense humidity and high levels of pollutants e.g. sea water or thermal baths.

**Technical Data:**

Parameters:	Value:
Steel thickness	0.9 mm
Reaction to fire	A1
Corrosion resistance class	Class B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.58 kN

**Packaging and Storage:**

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered and ventilated area.

**Safety recommendations:**

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.