

SELF-DRILLING SCREW TEX SUPER PREMIUM C5

Product description:

Self-drilling screw with high resistance against corrosion, designed for jointing metal profiles or for fixing direct suspension hanger to the profile CD 60.

Available Sizes: 4.2 x 13 mm



Standard Classification:

In compliance with **EN 14566:2008**

Type **TB**

Category for Protection Against Corrosion, acc. EN ISO 12944-2:

Class C5 Highest Level of Protection



Aggressive Environment Examples - Class C5:

- External
 - Industrial zones, coastal areas and buildings near the beach with high levels of salt in the air.
- Internal
 - Buildings and areas subject to constant condensation, intense humidity and high levels of pollutants e.g. sea water or thermal baths.


Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Storage:

Product	$d_w \times L_w$	Box
Self-drilling screw TEX 4.2 x 13 Super Premium C5	4.2 x 13 mm	1000 pcs

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area



Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.