

Adjusting Bracket

Technogips Pro Adjusting Bracket, ideal for directly suspension of CD 60 profile to solid walls and ceilings.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 75, 125, 150, 200, 250, 300 mm
Metal thickness: 0.8 mm



Standard Classification:

In compliance with EN 13964:2014




Advantages:

- ✓ Innovative, centrally positioned rib design, for increased stability and recommended load carrying capacity (min 0,40 kN)
- ✓ Uniform metal thickness of 0,8 mm, for added strength
- ✓ Easy levelling due to the shoulder positioned service holes
- ✓ Minimized loss of useful space in the room
- ✓ Quick and easy application

Technical Data:

Parameters:	
Steel thickness	0.8 mm
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.90 kN



Packaging and Storage:

Product	Dimensions L _w / d _w	Thickness	Box
Adjusting Bracket 75	70 / 60 mm	0.8 mm	100 pcs
Adjusting Bracket 125	120 / 60 mm	0.8 mm	100 pcs
Adjusting Bracket 150	150 / 60 mm	0.8 mm	100 pcs
Adjusting Bracket 200	200 / 60 mm	0.8 mm	100 pcs
Adjusting Bracket 250	250 / 60 mm	0.8 mm	100 pcs
Adjusting Bracket 300	300 / 60 mm	0.8 mm	100 pcs

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered and ventilated area.

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©