

## Acoustic Rotary Hanger

Acoustic Rotary Hanger for suspension of CD 60 Premium profile structure to the main ceiling (concrete, wooden grid, etc.). Thanks to the integrated rubber damper at its base, the Acoustic Adjusting Bracket improves effectively sound proofing of premises by stopping the spread of impact noise and vibrations from the floor and ceiling.



### Standard Classification:

In compliance with EN 13964:2014



### Advantages:

- ✓ Recommended load-bearing capacity of max 0.15 kN | 15 kg
- ✓ A stable spring for a precise levelling of the suspended ceiling level

### Technical Data:

Parameters:	
Steel thickness	0.70 mm
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.15 kN
Max. load-bearing capacity admF	0.15 kN

### Packaging and Storage:

Product	Thickness	Box
Acoustic Rotary Hanger	1.00 mm	100 pcs

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered and ventilated area.

### Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2022©