

TITAN[®] Screw TN

Technogips Pro Titan Screw TN, designed with high-low thread for fixing high density plasterboards (Titan Board DFH11R, Sound Comfort Extra DF, etc.) to metal profiles with metal thickness up to 0.7 mm.

The black coloured, phosphate coating guarantees the vast corrosion resistance of the element.

Available Sizes: 3.9 x 25, 35mm



Standard Classification:

In compliance with EN 14566:2008 Type **TN**



Advantages:



✓ PH 2 screw bit included in every box



✓ Sharpened point and special high-low thread ease the puncture of the plasterboard and metal profile

Technical Data:

Parameters:	Specification:
Reaction to fire	A 1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Product	d _w x L _w	Box	Boxes in a carton
Drywall Screw 3.9 x 25	3.9 x 25 mm	1000 pcs	18
Drywall Screw 3.9 x 35	3.9 x 35 mm	1000 pcs	12

- ✓ Packaged in distinctive green Technogips Pro boxes with included PH2 screw bit
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2021©