


Premium Profile UD 27

Technogips Pro Premium Profile UD 27 (marginal) ideal for the construction of suspended ceilings and partition walls.

The specially designed 3D structure of the steel increases its material strength capacity and ensures uniformity and stability when perforating and fastening with drywall screws.

The distinctively grey colour, zink coating guarantees the profile to be vastly corrosion resistant.



Standard Classification:

In compliance with EN 14195:2015 & DIN 18182-1:2015,
Type: U 27/28/27




Advantages:

- ✓ 3D structure of the metal results in an increase of yield strength and the ease and durability in the application of Drywall Screws.
- ✓ Quick and easy installation of single or double layer suspended ceiling.
- ✓ Provides a steady and secure base for the installation of wall linings fastened with Adjusting Bracket.
- ✓ A vital component in each of the Technogips Pro high-performance systems for fire protection and sound insulation.
- ✓ Guaranteed uniformity of Zink coating.
- ✓ Lightweight with high strength.

Technical Data:

Technical characteristics	
Steel thickness	0.5 & 0.6 mm
Reaction to fire	A1
Scope of Zink coating	Z100(0.5) / Z140(0.6)
Yield Strength R _r , N/mm ²	140



Product	Dimensions A/B/C	Thickness	Length
Premium Profile UD 27	27/60/27 mm	0.5 & 0.6 mm	3 & 4 m

Packaging and Storage:

Product	Thickness	Length	Profiles / bunch	Profiles/bundle
Premium Profile UD 27	0.5 & 0.6 mm	3 & 4 m	16 pcs	192 pcs

Humidity and other atmospheric conditions can lead to the formation of white oxidised patches on the profile's surfaces. It's advisable to strictly follow the storage instructions prescribed on how to safely store the product:

- ✓ Store in a dry, covered and ventilated area.
- ✓ In the case of extended exposure to the natural elements (not recommended), the bundles will require to be positioned at a small angle for the collected water to drain.

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. October 2021©