

Cement Board Screw TN

Product description:

Cement Board Screw with a sharp point and high-low thread, with high resistance against corrosion, for fixing fiber cement boards to metal profiles with metal thickness up to 0.7 mm.

Phosphate coating with black color, guarantees protection against corrosion.

Available Sizes: 3.9 x 25, 35mm



Standard Classification:

In compliance with **EN 14566:2008**
Type **TN**

Advantages:



- ✓ PH 2 screw bit included in every box
- ✓ Sharp point and high-low thread for faster passage through the board and easier drilling of the metal profile

Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Storage:

Product	d _w x L _w	Box	Boxes in a carton
Cement Board Screw TN 3.9 x 25	3.9 x 25 mm	1000 pcs	18 units
Cement Board Screw TN 3.9 x 35	3.9 x 35 mm	1000 pcs	12 units

- ✓ Packaged in distinctive green Technogips Pro boxes with included PH2 screw bit
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.