

## Self-drilling Screw TEX

Technogips Pro Self-drilling Screw with a self-drilling point is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. Fasten elements with a collective thickness up to 2 mm.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 4.2 x 13 mm и 3.5 x 9.5 mm

4.2 x 13 mm



3.5 x 9.5 mm



### Standard Classification:

In compliance with EN 14566:2008 Type **LB**



### Advantages:



✓ PH 2 screw bit included in every box



✓ The button head of the screw ensures added strength to the fastening of the joint elements



✓ Self-drilling point and specially designed thread help to drill the metal profile directly, with ease.


### Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

### Packaging and Storage:

Product	d <sub>w</sub> x L <sub>w</sub>	Box	Boxes in a carton
Self-drilling Screw TEX 4.2 x 13	4.2 x 13 mm	1000 pcs	16
Self-drilling Screw TEX 3.5 x 9.5	3.5 x 9.5 mm	1000 pcs	42

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area



### Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©