

## Self-drilling Screw TEX with flat head

### Product description:

Special Self-drilling Screw TEX with flat head is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. Fasten elements with a collective thickness up to 2 mm.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 4.2 x 13 mm



### Standard Classification:

In compliance with **EN 14566:2008**  
Type **LB**



### Advantages:



✓ PH 2 screw plug



✓ Flat screw head to provide additional protection against cracks when installing gypsum plasterboards.



✓ Self-drilling point and specially designed thread help to drill the metal profile directly, with ease.

### Technical Data:

| Parameters:                         | Specification: |
|-------------------------------------|----------------|
| Reaction to fire                    | A1             |
| Corrosion resistance classification | 48 hrs         |
| Drilling time requirement           | < 2 sec        |

### Storage:

| Product                          | d <sub>w</sub> x L <sub>w</sub> | Box      | Boxes in a carton |
|----------------------------------|---------------------------------|----------|-------------------|
| Self-drilling Screw TEX 4.2 x 13 | 4.2 x 13 mm                     | 1000 pcs | 32 units          |

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

### Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.