

Rotary Hanger, Anchor Type

Technogips Pro Rotary Hanger, Anchor Type, ideal for the directly suspending a grid of CD 60 profile to a solid, concrete slab.

Specially designed supporting shoulder positioned in the lower half of the hanger for increased stability in a 2-point tie to CD 60 profile. The spring positioned in the lower half has two pre-cut surface holes of Ø 4mm to ensure a secure fixing to the Wire with Hook and Eye, while simultaneously it ensures an easy and precise levelling of the construction.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.



Metal gauge: 0.8 mm

Standard Classification:

In compliance with EN 13964:2014



Advantages:

- ✓ Increased load carrying capacity and added strength due to the larger metal gauge of 0.8 mm
- ✓ 2-point tie to profile CD 60
- ✓ Recommended load carrying capacity of max 0.25 kN
- ✓ A stable spring for a precise levelling of the suspended ceiling level
- ✓ Quick and easy application

Technical Data:

Parameters:	Specification:
Steel thickness	0.8 mm
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.25 kN
Max. Load-bearing capacity admF	0.42 kN

Packaging and Storage:

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©