

## Double Spring

Technogips Pro Double Spring, ideal for the secure suspension of wire with hook or eye extensions in suspended ceiling installations suspended from a concrete slab. Special, pre-cut service holes Ø 4 mm to ensure a secure fixing of the wires.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Metal gauge: 0.6 mm



### Standard Classification:

In compliance with EN 13964:2014



### Advantages

- ✓ Quick and easy application
- ✓ The suspension height is regulated with the highest precision in a steady tie with a wire with hook or eye
- ✓ Minimized loss of useful space in the room
- ✓ Regulates the material consumption

### Technical Data:

Parameters:	
Steel Thickness	0.6 mm
Material fire reaction class:	A1
Corrosion resistance class:	B
Recommended load carrying capacity F	0.40 kN
Max. load carrying capacity admF	0.46 kN

### Packaging and Storage:

- ✓ 100 units in every box. Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

### Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. June 2019©