

Nonius Hanger – Upper Part, Bottom Part and Bracket

Nonius hanger for direct suspension of CD 60 Premium profile structure to the main ceiling (concrete, wooden grid, etc.). It provides a durable and strong resistant to force tie with load-bearing capacity of 0.40 kN.



Nonius Hanger, Bottom Part has a specially designed, curved bottom part with four connection points for fixing to CD 60 Profile, ensuring optimal strength. The upper part has pre-cut service holes for increased precision in levelling of the construction.
Metal thickness: 0.8 mm

Nonius Hanger, Upper Part has multiple pre-cut service holes along the length of its body with three available lengths of 360, 460, 960 mm. It provides the tie between the metal structure of the suspended ceiling to the concrete slab.
Metal thickness: 0.8 mm



Nonius Hanger, Bracket used for fixing of the Upper and Bottom Part of the Nonius Hanger
Metal thickness: Ø 2.5 mm



The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Standard Classification:

In compliance with EN 13964:2014



Advantages:

- ✓ Ensures a stable and rigid tie in the construction of the suspended ceiling to the concrete slab.
- ✓ A component of the Technogips Pro high-performance systems for fire protection
- ✓ Recommended load carrying capacity max 0.4 kN
- ✓ Pre-cut service holes for increased precision in levelling of suspended ceilings.
- ✓ Quick and easy application

Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.43 kN

Packaging and Storage:

Product	Length	Thickness	Box
Nonius Hanger Bottom part	150 mm	0.8 mm	100 pcs
Nonius hanger Upper part 120	120 mm	0.8 mm	100 pcs
Nonius Hanger Upper part 360	360 mm	0.8 mm	100 pcs
Nonius Hanger Upper part 460	460 mm	0.8 mm	50 pcs
Nonius Hanger Upper part 960	960 mm	0.8 mm	25 pcs
Nonius Hanger Bracket	70 mm	0.8 mm	100 pcs

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

Safety Recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.